

CONO puro SMART



The smart built-in loudspeaker

Pure optics for pure sound - minimalist design and quick installation with twist lock

The new CONO puro built-in loudspeaker fits perfectly with the "small and simple" design trend. The diameter is just 150mm. The music is received reliably via 1.9 GHz radio technology. Furthermore, the new quick-release fastener eliminates the need for screws. This allows for quick installation and the screwless design also ensures simple elegance. The material thickness of the ring is kept to a minimum so that the speaker can lie flat on the ceiling. The ceiling cut-out required for installation is 120 mm and the installation depth is 140 mm.

Technical Data

Application

In-ceiling loudspeaker

Design

Colours



Dimensions

Ø 150 mm / h: 160 mm

Material housing

Ring made from glass fibre reinforced ABS plastic

Sound

Principle

360° - Speaker with integrated amplifier and wireless module

Output power

40 W RMS

Equipment

NewTec KA10 loudspeaker 50W 4Ω

Efficiency

85,5 dB

Maximum SRL

102 dB

Frequency response

105-20.000 Hz

Radio frequency

1,9 GHz n-DECT

Transmitter

SMARTplayer

Installation

Ceiling cut-out

120 mm

Ceiling thickness

min. 6 mm / max. 25 mm

Installation depth

140 mm

Weight

648 g

Power supply

AC 100-240 V; 50/60 Hz; 0.5 A

Connections

Connection terminal